

View Online at <https://aerobasegroup.com/nsn/5935-01-013-3753>

Body Style:

Straight type

Overall Length:

Between 1.490 inches and 1.510 inches

Overall Height:

Between 0.635 inches and 0.650 inches

Overall Width:

0.240 inches

Environmental Protection:

Humidity resistant and shock proof and thermal shock resistant and vibration resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

Between 0.170 inches and 0.180 inches

Distance Between Mounting Facility Centers:

Between 1.244 inches and 1.256 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-20693 military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-20693 spec.