NSN 5935-01-013-4466

Thread Class: 2a and 2b

Body Style:

Thread Direction:

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-013-4466

Straight shape, internal coupling
Overall Length:
1.370 inches
Overall Diameter:
0.906 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
40456 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Length:
0.290 inches and 0.290 inches
Thready Qty Per Inch (tpi):
24 and 24
Thread Size:
0.625 inches and 0.688 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end

NSN 5935-01-013-4466Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Shell Material Specification:
Qq-a-200/8, alloy 6061 federal specification single material response
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.025 gold grains, troy and 0.025 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-a-8625 spec.