Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-013-4478

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 0.535 inches and 0.545 inches
Overall Height:
0.250 inches
Overall Width:
0.250 inches
Environmental Protection:
Corrosion resistant
Threaded Device Type:
Mounting bushing
Mating End Quantity:
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring friction
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Length:
0.168 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:

Plastic polytetrafluoroethylene single mating end

Electrical Receptacle Connector - Page 2 of 2



## **Terminal Type:** Tab, solder lug single mating end single contact grouping **Contact Material Specification:** Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Gold and copper **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Insert Material Specification:** Mil-p-19468 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19468 spec.