

View Online at <https://aerobasegroup.com/nsn/5935-01-013-7215>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling strain relief

**Overall Length:**

4.384 inches

**Overall Height:**

2.250 inches

**Overall Width:**

2.250 inches

**Environmental Protection:**

Heat resistant and moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.173 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.750 inches

**Distance From Mounting Shoulder To Front Face:**

0.875 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32-17 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

135.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Cable clamp

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

2.000 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0