## NSN 5935-01-013-8366

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-013-8366 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.230 inches and 1.270 inches **Bushing Diameter:** 0.500 inches **Overall Height:** Between 1.230 inches and 1.270 inches **Overall Width:** Between 1.230 inches and 1.270 inches **Unthreaded Mounting Hole Diameter:** Between 0.136 inches and 0.146 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.870 inches and 0.880 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.870 inches and 0.880 inches **Distance From Mounting Shoulder To Front Face:** Between 0.600 inches and 0.640 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size: Terminal Location:** Back single mating end single contact grouping

0.500 inches

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-013-8366

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Glass single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Metal
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Contact designation lgh-1
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0