

View Online at <https://aerobasegroup.com/nsn/5935-01-014-1481>

**Body Style:**

Straight shape

**Overall Length:**

1.062 inches

**Overall Height:**

0.576 inches

**Overall Width:**

0.250 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

5 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

25.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -40.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Printed circuit single mating end all contact groupings

**Included Contact Quantity:**

4 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end 1st contact grouping

**Special Features:**

Female contact in pos no. 1

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.