## NSN 5935-01-014-2260

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-014-2260

**Body Style:** 

Straight shape

**Overall Length:** 

Between 4.993 inches and 5.017 inches

**Overall Width:** 

0.248 inches

**Environmental Protection:** 

Shock resistant and vibration proof

**Unthreaded Mounting Hole Diameter:** 

Between 0.093 inches and 0.103 inches

**Distance Between Mounting Facility Centers:** 

Between 4.710 inches and 4.720 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

110 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.110 gold grains, troy

## NSN 5935-01-014-2260

Electrical Receptacle Connector - Page 2 of 2



Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/24 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

Mil-std (military Standard): Mil-m-14 spec.

Fiig: A039b0

**Precious Material:**