NSN 5935-01-014-2611

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-014-2611 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 1.063 inches **Mounting Bushing Length:** 0.344 inches **Body Length:** 0.875 inches **Overall Diameter:** 0.563 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 5000.0 ac **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 0.161 inches single finger **Finger Accommodation Length:** 0.562 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.094 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material:

Plastic, polyamide insulator

NSN 5935-01-014-2611

Tip Jack - Page 2 of 2

A03400



Material:
Plastic polyamide insulator
Precious Material And Location:
Spring surface gold and spring surface silver
Precious Material And Weight:
$0.005 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.005 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Surface Treatment:
Gold and silver spring
Surface Treatment:
Gold spring and silver spring
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: