NSN 5935-01-014-4805

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-014-4805

Body Style: Straight shape **Overall Length:** Between 1.175 inches and 1.185 inches **Overall Height:** 0.385 inches **Overall Width:** Between 0.203 inches and 0.213 inches **Environmental Protection:** Corrosion resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.089 inches and 0.094 inches **Distance Between Mounting Facility Centers:** Between 0.960 inches and 0.970 inches **Mating End Quantity: Contact Position Arrangement Style:** 25 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Shell Material:** Aluminum alloy a380.0 **Shell Surface Treatment:** Nickel **Shell Material Specification:**

Qq-a-591, alloy a380 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg military specification single material response single mating end

NSN 5935-01-014-4805

Electrical Receptacle Connector - Page 2 of 2



25 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Wire leads 18.0 in. Long

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.