NSN 5935-01-014-4810

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-014-4810

Body Style:
Straight shape
Overall Length:
5.950 inches
Overall Height:
0.896 inches
Overall Width:
0.420 inches
Unthreaded Mounting Hole Diameter:
Between 0.140 inches and 0.146 inches
Distance Between Mounting Facility Centers:
5.700 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
2 polarization posts
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
$Mil-g-45204, type\ 2, class\ 1\ military\ specification\ 1st\ treatment\ response\ single\ mating\ end\ single\ contact\ grouping\ and\ qq-n-290\ federal$
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping

Shell Material:

Guide Design And Location:

D shape socket left-hand at 5 oclock and d shape socket right-hand at 5 oclock

Aluminum

NSN 5935-01-014-4810

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2 class 2 military specification single treatment response
Shell Material Specification:
Qq-a-200/8 federal specification single material response or qq-a-200/9 federal specification single material response
Insert Material Specification:
Mil-m-20693 cmpsn military specification single material response single mating end
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.