## NSN 5935-01-014-7788

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-014-7788 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.230 inches **Overall Diameter:** 1.391 inches **Environmental Protection:** Pressure proof and humidity resistant and shock proof and vibration resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-32 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.290 inches **Thread Size:** 1.062 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-014-7788

Electrical Plug Connector - Page 2 of 2



| Shell Material:  |
|--|
| Aluminum alloy   |
| Shell Material Specification:  |
| Qq-a-367 federal specification single material response  |
| Included Contact Quantity:   |
| 32 single mating end single contact grouping   |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.032 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Unef   |
| Specification Data:  |
| 81349-mil-c-83723 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |
| Mil-g-45204 spec.  |