

View Online at <https://aerobasegroup.com/nsn/5935-01-014-7826>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.326 inches

Overall Height:

Between 4.303 inches and 4.333 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Vibration resistant and fungus proof and shock proof

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 4.021 inches and 4.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.713 inches and 0.723 inches

Distance From Mounting Shoulder To Front Face:

Between 0.050 inches and 0.070 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

3

Contact Position Arrangement Style:

"106, a106" all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

5.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1100.0 all mating ends all contact groupings

Polarization Method:

2 polarization posts

Shell Type:

Solid

Thread Size:

0.112 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends

Terminal Type:

Crimp all mating ends all contact groupings

Contact Material Specification:

Qq-c-533 federal specification single material response all mating ends all contact groupings

Shell Material:

Aluminum alloy a380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Material Specification:

Qq-a-591, alloy a380 federal specification single material response

Insert Material Specification:

Mil-m-14, ty @sdg-f military specification single material response all mating ends

Included Contact Quantity:

318 all mating ends all contact groupings

Included Contact Type:

Round socket all mating ends all contact groupings

Special Features:

Polarized at position 83

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.318 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.