

NSN 5935-01-014-7827 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-014-7827 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:**

1.326 inches **Overall Height:**

Between 4.303 inches and 4.333 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Vibration resistant and fungus proof and shock proof

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 4.021 inches and 4.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.713 inches and 0.723 inches

Distance From Mounting Shoulder To Front Face:

Between 0.050 inches and 0.070 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

Contact Position Arrangement Style:

8 2nd mating end

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1100.0 3rd mating end all contact groupings

Polarization Method:

2 polarization posts

Shell Type:

Solid

Thread Size:

0.112 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

NSN 5935-01-014-7827

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate all mating ends
Terminal Type:
Crimp all mating ends all contact groupings
Contact Material Specification:
Qq-c-533 federal specification single material response all mating ends all contact groupings
Shell Material:
Aluminum alloy a380.0
Shell Surface Treatment:
Cadmium and chromate
Shell Material Specification:
Qq-a-591, alloy a380 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response all mating ends
Special Features:
All polarization posts polarized at position 68
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.114 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.