

View Online at <https://aerobasegroup.com/nsn/5935-01-014-7837>

**Body Style:**

Straight shape

**Overall Length:**

Between 1.175 inches and 1.185 inches

**Overall Height:**

0.385 inches

**Overall Width:**

Between 0.203 inches and 0.213 inches

**Environmental Protection:**

Vibration resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.089 inches and 0.094 inches

**Distance Between Mounting Facility Centers:**

Between 0.960 inches and 0.970 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Shell Surface Treatment Specification:**

Mil-f-14072, finish no. E300 military specification single treatment response

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

25 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Wire leads 18.0 in. Long

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.025 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.