## NSN 5935-01-014-7840



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-014-7840 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.125 inches **Overall Diameter:** 0.578 inches **Environmental Protection:** Waterproof **Mounting Facility Thickness:** Between 0.031 inches and 0.063 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Crimp type Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping Copper alloy single mating end single contact grouping

**Contact Material: Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** 

Plastic tetrafluoroethylene single mating end

## NSN 5935-01-014-7840

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Shell Material Specification:
Qq-b-626 federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0