

View Online at <https://aerobasegroup.com/nsn/5935-01-014-9876>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Wall type w/ or w/o cover

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.281 inches

Environmental Protection:

Heat resistant

Unthreaded Mounting Hole Diameter:

0.138 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.812 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 10-20, 10-50" single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

50.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Screw single mating end single contact grouping

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81348-w-c596/36 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0