Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-015-1714

#### **Body Style:**

Angle shape, pcb type

### **Overall Length:**

4.150 inches

### **Overall Height:**

0.359 inches

**Overall Width:** 

#### 0.550 inches

#### **Environmental Protection:**

Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

#### **Unthreaded Mounting Hole Diameter:**

#### 0.120 inches

**Distance Between Mounting Facility Centers:** 

#### 3.900 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Friction

#### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Insert Material:

Plastic polyphenylene single mating end

## Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Printed circuit single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



**Guide Design And Location:** D shape socket left-hand top at 9 oclock and d shape pin right-hand bottom at 9 oclock **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:** 66 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.066 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.