## NSN 5935-01-015-1974

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-015-1974

**Body Style:** 

Pcb, external coupling

**Overall Length:** 

0.485 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.200 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Shell Surface Treatment:** 

Silver

**Shell Surface Treatment Specification:** 

Qq-s-365, type 2, grade b federal specification single treatment response

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold and contact surface silver

**Precious Material And Weight:** 

0.005 gold grains, troy and 0.100 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

## NSN 5935-01-015-1974

Electrical Receptacle Connector - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A039b0