## NSN 5935-01-015-3566

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-015-3566

**Body Style:** 

Straight shape, flush mount

**Overall Length:** 

1.326 inches

**Overall Height:** 

Between 3.060 inches and 3.090 inches

**Overall Width:** 

Between 3.845 inches and 3.875 inches

**Environmental Protection:** 

Shock proof and thermal shock resistant and vibration resistant and salt water resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.925 inches and 0.935 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.050 inches and 0.070 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

8 1st mating end

**Contact Removability:** 

Removable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.0 2nd mating end 2nd contact grouping

**Polarization Method:** 

2 polarization posts

Shell Type:

Solid

**Terminal Location:** 

Back all mating ends all contact groupings

**Contact Material:** 

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:** 

Gold all mating ends all contact groupings

**Insert Material:** 

Plastic diallyl phthalate all mating ends

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends all contact groupings

**Terminal Type:** 

Crimp all mating ends all contact groupings

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-015-3566

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response all mating ends
Special Features:
Polarized at position 02
Precious Material And Location:
Contact sufaces gold
Precious Material And Weight:
0.287 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):