

View Online at <https://aerobasegroup.com/nsn/5935-01-016-0146>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Pcb, external coupling

Overall Length:

0.662 inches

Overall Height:

0.250 inches

Overall Width:

0.250 inches

Environmental Protection:

Shock proof and thermal shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.200 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.