NSN 5935-01-016-1160

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-1160

| View Online at https://aerobasegroup.com/nsn/5935-01-016-1160 |
|---|
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 67 single mating end |
| Contact Removability: |
| Removable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end 1st contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 1900.0 single mating end 2nd contact grouping |
| Polarization Method: |
| 3 polarization posts |
| Shell Type: |
| Solid |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings and silver single mating end all contact groupings |
| Insert Material: |
| Plastic phenolic single mating end |
| Terminal Type: |
| Crimp single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 64 single mating end 1st contact grouping |
| Included Contact Type: |
| Round pin single mating end all contact groupings |
| Precious Material And Location: |
| Contact surface gold and contact surface silver |
| Precious Material: |
| Gold and silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5935-01-016-1160

Electrical Receptacle Connector - Page 2 of 2



Fiig:

A039b0