

View Online at <https://aerobasegroup.com/nsn/5935-01-016-1692>

Body Style:

Straight shape, flush mount

Overall Length:

1.326 inches

Overall Height:

Between 3.060 inches and 3.090 inches

Overall Width:

Between 3.845 inches and 3.875 inches

Environmental Protection:

Moisture proof and salt water resistant and thermal shock resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.925 inches and 0.935 inches

Distance From Mounting Shoulder To Front Face:

Between 0.050 inches and 0.070 inches

Mating End Quantity:

4

Contact Position Arrangement Style:

8 1st mating end

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

5.0 4th mating end all contact groupings

Polarization Method:

2 polarization posts

Shell Type:

Solid

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends

Terminal Type:

Crimp all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response all mating ends

Special Features:

Polarized at position 05

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.326 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.