## NSN 5935-01-016-1987

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-1987 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.880 inches **Overall Height:** 0.624 inches **Overall Width:** 0.280 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance Between Mounting Facility Centers:** 0.625 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Length:** 0.220 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** 

Solder well single mating end single contact grouping

**Included Contact Quantity:** 

14 single mating end single contact grouping

## NSN 5935-01-016-1987

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0