

View Online at <https://aerobasegroup.com/nsn/5935-01-016-2464>

Body Style:

Straight shape duplex

Overall Width:

1.328 inches

Environmental Protection:

Heat resistant

Distance Between Mounting Facility Centers:

3.281 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

2 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

15.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Contact twistlock

Terminal Location:

Side single mating end 2nd contact grouping

Contact Material:

Copper alloy all mating ends all contact groupings

Terminal Type:

Screw all mating ends all contact groupings

Included Contact Quantity:

1 2nd mating end 2nd contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0