## NSN 5935-01-016-3632

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-3632

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.234 inches
Overall Diameter:
0.984 inches
Environmental Protection:
Moisture resistant and vibration resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
13089 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
14.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thread Size:
0.562 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Aluminum alloy

## **NSN 5935-01-016-3632**Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.013 gold grains, troy and 0.013 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 spec.