

View Online at <https://aerobasegroup.com/nsn/5935-01-016-3638>

**Body Style:**

Straight shape duplex

**Environmental Protection:**

Heat resistant

**Distance Between Mounting Facility Centers:**

3.281 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

"3, 6-15, 6-30" all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 all mating ends all contact groupings

**Polarization Method:**

Contact

**Terminal Location:**

Side single mating end 2nd contact grouping

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Terminal Type:**

Screw all mating ends all contact groupings

**Included Contact Quantity:**

2 2nd mating end 2nd contact grouping

**Included Contact Type:**

Flat socket 2nd mating end 2nd contact grouping

**Test Data Document:**

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-w-c-596/16 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0