Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-3814

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

2.406 inches

Overall Height:

0.890 inches

Overall Width:

1.250 inches

Distance Between Mounting Facility Centers:

1.969 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

66 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Jackscrew and shell

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.338 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end



Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize Shell Guide Type And Location Designator: G pin Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 66 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Jackscrew type-female and location-right handandjackscrew type-male and location-left hand **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.066 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0