# NSN 5935-01-016-7571

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-7571

Thread Class:
2b and 2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
1.430 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.203 inches
Overall Height:
0.630 inches
Overall Width:
0.500 inches
Environmental Protection:
Corrosion resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.093 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.343 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.250 inches
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-01-016-7571

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

## **Insert Material Specification:**

Mil-p-19833, ty gdi-30f military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

50 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-male and location-right handandjackscrew type-female and location-left hand

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.050 gold grains, troy

## **Precious Material:**

Gold

## **Thread Series Designator:**

Unc and unc and unc

**Shelf Life:** 

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.