Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-8611

| Body Style:   |
|---|
| Straight type   |
| Overall Length:   |
| 2.456 inches  |
| Overall Width:  |
| 0.343 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.128 inches  |
| Distance Between Mounting Facility Centers:   |
| 2.156 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 1 row of contacts inserted board single mating end  |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping                     |
| Insert Material:  |
| Plastic diallyl phthalate single mating end   |
| Terminal Type:  |
| Solder well single mating end single contact grouping   |
| Contact Material Specification:   |
| Qq-b-750 comp a federal specification single material response single mating end single contact grouping                |
| Insert Material Specification:<br>Mil-m-14 type sdg-f military specification single material response single mating end |
| Included Contact Quantity:  |
| 10 single mating end single contact grouping  |
| Included Contact Type:  |
| Leaf spring single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.010 gold grains, troy   |
| Precious Material:  |
| Gold  |
|   |

Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.