## NSN 5935-01-016-9949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-016-9949 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.310 inches **Overall Height:** 0.720 inches **Overall Width:** 0.380 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thread Length: 0.230 inches **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-01-016-9949

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Plastic diallyl phthalate and glass fiber
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0