

View Online at <https://aerobasegroup.com/nsn/5935-01-017-1197>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

3.875 inches

**Overall Height:**

Between 0.681 inches and 0.726 inches

**Overall Width:**

Between 0.333 inches and 0.353 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.119 inches

**Distance Between Mounting Facility Centers:**

Between 3.398 inches and 3.406 inches

**Board Accommodated Length:**

2.966 inches single board and 2.978 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping or copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

18 single mating end single contact grouping

**Included Contact Type:**

Flat socket single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.