

View Online at <https://aerobasegroup.com/nsn/5935-01-017-3292>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, flush mount

Overall Height:

Between 3.359 inches and 3.391 inches

Overall Width:

Between 3.922 inches and 3.954 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.865 inches and 2.885 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.995 inches and 1.005 inches

Distance From Mounting Shoulder To Front Face:

Between 0.057 inches and 0.067 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

50 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

15.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1500.0 all mating ends all contact groupings

Polarization Method:

1 polarization post

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

12

Thread Size:

0.312 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends

Terminal Type:

Solder well all mating ends all contact groupings

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

Included Contact Type:

Round socket all mating ends all contact groupings

Special Features:

Eight 0.144 in. Diameter mtg holes

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.100 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0