NSN 5935-01-017-3703

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-017-3703 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.125 inches **Overall Diameter:** 0.688 inches **Environmental Protection:** Shock proof and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.823 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:**

Round w/flat

NSN 5935-01-017-3703

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A039b0