Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-017-4172

#### **Body Style:**

Straight shape

## **Overall Length:**

Between 2.073 inches and 2.103 inches

## **Overall Height:**

0.694 inches

## **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

Between 1.847 inches and 1.857 inches

#### Mating End Quantity:

**Contact Position Arrangement Style:** 

25 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Polarization Method:**

Mating end

#### Shell Type:

Solid

1

#### **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Pin single mating end single contact grouping

# Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

# Included Contact Quantity:

25 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping



## Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.025 gold grains, troy

Precious Material:

Gold

## Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-24308/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0