NSN 5935-01-017-5051

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-017-5051

Body Style: Straight shape, rectangular **Overall Length:** 0.890 inches **Overall Height:** 1.100 inches **Overall Width:** 2.000 inches **Environmental Protection:** Dripproof and shock proof and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.700 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Screw **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Included Contact Quantity:** 106 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-017-5051

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.106 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.