## NSN 5935-01-017-5890

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-017-5890 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.766 inches **Overall Diameter:** 1.156 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 14-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.812 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-017-5890

Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No
Fiig:
A039b0