## NSN 5935-01-017-5896

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-017-5896 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.125 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Environmental Protection:** Moisture proof and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.975 inches and 0.985 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-27 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

## NSN 5935-01-017-5896

Electrical Receptacle Connector - Page 2 of 3



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches and 0.625 inches
Thready Qty Per Inch (tpi):
10 and 10
Thread Size:
1.250 inches and 1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Sae ca187 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.014 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Double stub and double stub
Shelf Life:
N/a

-

Unit Of Measure:

## NSN 5935-01-017-5896

Electrical Receptacle Connector - Page 3 of 3



Demilitarization:

No

Fiig:

A039b0