Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-018-1466

Body Style:

Straight shape, external coupling

Overall Length:

1.109 inches

Overall Height:

1.188 inches

Overall Width:

1.188 inches

Environmental Protection:

Corrosion resistant and moisture resistant and oil resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Distance be

0.906 inches

Distance From Mounting Shoulder To Front Face:

0.531 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

197p single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

40.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Ball

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end



Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0