NSN 5935-01-018-3045

Thread Class: 2a and 2b

Thread Direction:

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-018-3045

Body Style:
Straight shape w/clamp
Overall Length:
2.312 inches
Overall Height:
2.467 inches
Overall Width:
0.828 inches
Environmental Protection:
Moisture resistant and vibration resistant
Cable Entrance Diameter:
0.340 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
42 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Hood, top opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thread Size:
0.138 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-018-3045Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy 5052
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
42 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.042 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc and unc
Specification Data:
81349-mil-c-28748 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.