NSN 5935-01-018-4563

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-018-4563 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape center screwlock **Overall Length:** Between 2.115 inches and 2.135 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.745 inches and 1.755 inches **Overall Height:** 1.520 inches **Overall Width:** Between 0.820 inches and 0.840 inches **Environmental Protection:** Moisture resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss Shell Type: Solid Thread Size: 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

Cadmium

Shell Surface Treatment:

NSN 5935-01-018-4563

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 1 federal specification single treatment response
Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-28748 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: