NSN 5935-01-019-5166

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-019-5166

| Body Style: |
|---|
| Straight shape |
| Overall Length: |
| 0.700 inches |
| Overall Height: |
| 0.575 inches |
| Overall Width: |
| 0.400 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.097 inches and 0.102 inches |
| Distance Between Mounting Facility Centers: |
| 0.500 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of independent contacts inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Shell Type: |
| Solid |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic polyamide single mating end |
| Terminal Type: |
| Wire wrap single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Shell Surface Treatment Specification: |
| Mil-a-8625, type 2, class 2 military specification single treatment response |
| Included Contact Quantity: |
| 6 single mating end single contact grouping |

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-019-5166

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.030 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-a-8625 spec.