Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-019-5184

## **Body Style:** Straight shape threaded **Overall Length:** 0.688 inches **Overall Diameter:** Between 1.146 inches and 1.167 inches **Distance From Mounting Shoulder To Front Face:** Between 0.312 inches and 0.322 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 850.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Glass single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Included Contact Quantity:** 26 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round



Included Contact Type:

Round pin single mating end single contact grouping

## **Special Features:**

Solder flange mounted

**Precious Material And Location:** 

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0