## NSN 5935-01-019-6553

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-019-6553 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 0.405 inches and 0.455 inches **Overall Diameter:** Between 0.307 inches and 0.317 inches **Environmental Protection:** Corrosion resistant and moisture resistant and vibration resistant **Cable Entrance Diameter:** Between 0.089 inches and 0.092 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** 

Plastic tetrafluoroethylene single mating end

# NSN 5935-01-019-6553

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Steel comp 303

**Shell Surface Treatment:** 

Gold

**Shell Material Specification:** 

Qq-s-764, cond a federal specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Included Contact Type:** 

Coaxial pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surface and shell surface gold

**Precious Material And Weight:** 

0.105 gold grains, troy

Precious Material:

Gold

**Thread Series Designator:** 

Uns

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.