# NSN 5935-01-019-9721

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-019-9721 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flange mount **Overall Length:** 0.625 inches **Bushing Diameter:** 0.250 inches **Overall Height:** 0.500 inches **Environmental Protection:** Salt water resistant and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.102 inches **Distance Between Mounting Facility Centers:** 0.481 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Osm single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping

**Contact Material: Contact Surface Treatment:** 

Copper alloy single mating end single contact grouping

Gold single mating end single contact grouping

# NSN 5935-01-019-9721

Electrical Receptacle Connector - Page 2 of 2



Insert	Mata	rial:
msert	wate	Hai.

Plastic fluorocarbon single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Steel comp 303

#### **Shell Material Specification:**

Qq-s-764, type 303 cond a federal specification single material response

#### **Included Contact Quantity:**

1 single mating end single contact grouping

#### **Included Contact Type:**

Coaxial socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.001 gold grains, troy

# **Precious Material:**

Gold

# **Thread Series Designator:**

Unef

# Shelf Life:

N/a

#### **Unit Of Measure:**

## Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.