NSN 5935-01-020-1493

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-020-1493 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.340 inches **Overall Height:** 1.351 inches **Overall Width:** 1.351 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.775 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-38 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 98.0 and 152.0 and 268.0 and 338.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28

Thread Size:

1.125 inches

NSN 5935-01-020-1493

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-367, comp 6061, t6 federal specification single material response
Included Contact Quantity:
38 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.038 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-g-45204 spec.

Mil-std (military Standard):