Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-020-2579

Thread Class: 2b Thread Picetion: Right-hand Seal Material: Rubhised Items: Purbised Items: Purbised Items: Protective cap Coverall Length: 1.500 inches Coverall Quantity: 1 1.500 inches Size Designation: 10 Coverall Length: 100 Incoverance Coverance		
Piread Direction: Right-hand Sead Material: Rubber, sillcone base Protective cap Overall Length: 1.500 inches Overall Diameter: 1.200 inches Cable Opening Diameter: 1.201 inches Cable Opening Ouantity: 1.201 inches Cable Opening Ouantity: 1 1 Sead Type: Preformed packing Size Dasignation: 1 1 Subited Coupling Thread Park (Interpreter) 1 1 Star Specific Type And Quantity: 1 1 1 Subited Coupling Thread Park (Interpreter) 20 and 20 Thread Star Star Type: 20 and 20 Star Type: 20 and 20 Star Type: 20 and 20 Star Type: Star Type: Star Type: Star Type: Star Type: Star Type: Quantity: Star Type: Star Type: Star Type: Star Type: Star Type: Star Typ		
Right-hand Seid Material: Rubber, sillicone base Furnished Items: Profective cap Overall Length: 1.500 inches Overall Diameter: 1.250 inches Cable Opening Diameter: 0.427 inches Cable Opening Diameter: 0.427 inches Sall Opening Quantity: 1 Sall Opening Quantity: 1 Sei Designation: 10 Size Designation: 10 10 Size Designation: 10 10 Size Designation: 10 10 Size Designation: 10 11 Size Designation: 10 Size Designation: 10 11 Size Designation: 11 120 120 120 121 Size Designation: 121 122 123 123 124 Mended coupling 125 125 126 Size Designation: 127 128 Size Designation: 129 129 129 129 129 129 129 129 129 129 129 129 129 129 129 <th></th> <th></th>		
Sel Material: Rubber, silicone base Funcished Items: Protective cap Protective cap Overall Langth: 1.500 inches Overall Diameter: 1.250 inches Cable Opening Diameter: 0.427 inches Cable Opening Diameter: 0.427 inches Sel Type: Preformed packing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Threaded coupling Quantical Surface Treatment: Quanting Surface Treatment: Cadmim Surface Treatment: Cadmim Straight type wistrain relief		
Rubber, silicone base Furished items: Protective cap Overall length: 1.500 inches Overall Jointeer: 1.250 inches Cable Opening Diameter: 0.427 inches Cable Opening Ouantity: 0.427 inches Seal Type: Preformed packing Seal Type: Preformed packing State Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.338 inches Material: Aluminum alby Surface Treatment: Cadmium Strig Designator: Strig Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Na Unit of Measure: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Na Unit of Measure:		
Funished Items: Protective cap Overall Length: 1.500 inches Vorrall Diameter: 1.250 inches Cable Opening Diameter: 0.427 inches Cable Opening Quantity: 0.427 inches Seal Type: Preformed packing Star Designation: 1 Star Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Protein (tpl): 20 and 20 Pread Size: 0.938 inches Material: Aduminum alloy Surface Treatment: Cadmium Strides Treatment: Cadmium Thread Size: Out for Exercement: Cadmium Strides Treatment: Cadmium Thread Size: Cadmium Thread Size: Out for Exercement: Cadmium Thread Size: Cadmium Thread Size: Cadmium <t< th=""><th></th><th></th></t<>		
Protective cap Protective cap		
Overall Length:1.500 inchesOverall Diameter:1.250 inchesCable Opening Diameter:0.427 inchesCable Opening Quantity:1Seal Type:Preformed packingSize Designation:16Mouning Facility Type And Quantity:1 threaded coupingThready Qty Per Inch (tp)):20 and 20Prieradi Size:0.398 inchesMaterial:Aluminu alloySurface Treatment:CadmiumStyle Designator:Straight type wistrain reliefSurface Treatment:CadmiumThread Straige:Out of Measure:Via CoupingStraight type wistrain reliefSurface Treatment:CadmiumThread Straige Designator:Straight type wistrain reliefMaterial:NaUnit of Measure:ViaDin Couping		
1.500 inclust 0.4zrl Diameter: 1.250 inclust Cable Opening Diameter: 0.427 inclust Cable Opening Quantity: Cable Opening Quantity: Cable Opening Quantity: Seal Type: Preformed packing Ster Designation: 10 Ste Designation: 13 Mounting Facility Type And Quantity: 1 threaded coupling Thready City Pe And Quantity: 1 threaded coupling Munting Facility Type And Quantity: 2 data 20 Thread Size: 0.303 inclusts Material: Aurninum alloy Surface Treatment: Cadmium Surface Treatment: Cadmium Thread Sizes Designator: Cadmium Thread Size Designator: Cadmium Thread Size Designator: Cadmium Thread Size Designator: Unit of Measure: Va Unit Of Measure: Pace Pace Pa		
Overall Diameter:1.250 inchesCable Opening Diameter:0.427 inchesCable Opening Quantity:1Seal Type:Preformed packingSize Designation:16Mounting Facility Type And Quantity:1 threaded couplingThreaded couplingThreaded couplingCheed Size:0.393 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStraight type w/strain reliefSurface Treatment:CadmiumThread Seeins Designator:Naterial:Naterial:Naterial:Surface Treatment:CadmiumStraight type w/strain reliefSurface Treatment:CadmiumThread Seeins Designator:Naterial:Naterial:Naterial:CadmiumThread Seeins Designator:Naterial:Naterial:Naterial:Naterial:Naterial:Paterial:Naterial:Paterial:Naterial:Pateria:Nateria:Pateria:Nateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria:Pateria: <t< th=""><th></th><th></th></t<>		
1.250 inches Cable Opening Diameter: 0.427 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Striaght type w/strain relief Surface Treatment: Cadmium Thread Seneis Designator: Cadmium Thread Seneis Designator: Naterial: Naterial: Cadmium Thread Seneis Designator: Inter Seneis Designator: Naterial: Naterial: Naterial: Naterial: Inter Seneis Designator: Inter Seneis Designator: Inter Seneis Designator: Inter Seneis Designator: Naterial: Naterial:		
Cable Opening Diameter: 0.427 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Striface Treatment: Cadmium Striface Treatment: Cadmium Striface Treatment: Cadmium Striface Treatment: Cadmium Thread Series Outroet Treatment: Cadmium Thread Series Designator: Cadmium	C	Overall Diameter:
0.427 indes Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Y Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Seles Duried Treatment: Cadmium Thread Seles Designator: Cadmium Thread Seles Designator: Cadmium Thread Seles Designator: Cadmium Thread Seles Designator: Chef Sheff Life: Na Dit Of Measure: - Penilitarization:	1	.250 inches
Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 10 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Straight type wistrain relief Surface Treatment: Cadmium Straight type migent the field Material: I thread Series Designator: Cadmium Thread Series Designator: Unef Surface Treatment: I the Add Series Designator: Unef Surface: I the Series Designator: Unef Surface: I the Series Designator: I the Series Designator: <td< th=""><th>C</th><th>Cable Opening Diameter:</th></td<>	C	Cable Opening Diameter:
1 Seal Type: Preformed packing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Straight type w/strain relief Surface Treatment: Cadmium Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: Na Unef Shelf Life: Na Unit Of Measure: Emilitarization:	0	.427 inches
Seal Type: Preformed packing Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Cadmium Strafact Treatment: Cadmium Straface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: Na Unt Of Measure: - Pemilitarization:	C	Cable Opening Quantity:
Preformed packing Size Designation: IG Gunting Facility Type And Quantity: I threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Strlaght type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: Na Unef Sheff Life: Na Unef Cadmium: - Unet Cadmium:	1	
Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: N/a Unef Sheff Life: N/a Unit Of Measure: - - Pemilitarization:	S	Seal Type:
16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Intread Series Designator: Unef Shef Life: Na Unef Shef Life: Na Duef Shef Life: Duef Duef Shef Life: Duef <th>F</th> <th>Preformed packing</th>	F	Preformed packing
Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.308 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Itread Series Designator: Unef Shelf Life: Na Unef Shelf Life: Na Ditt Of Measure: T Temasure: Totaget Series Surface Treatment: Unef Shelf Life: Na Ditt Of Measure: T Termater Surface Treatment: Surface Treatment: Surface Treatment: Unef Surface Treatment: Surface Treatment: Surface Treatment: Surface Treatment: Surface Treatment: Surface Treatment: <	S	ize Designation:
1 threaded coupling Thready Qty Per Inch (tpi): 20 and 20 Thread Size: 0.938 inches 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: - Cadmium - Demilitarization:	1	6
Thready Qty Per Inch (tpi):20 and 20Thread Size:0.938 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumInefStraight type w/strain reliefSurface Treatment:CadmiumInfer ComparisonStraight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnef fullShelf Life:N/aDint of Measure:<	N	Iounting Facility Type And Quantity:
20 and 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Straight type w/strain relief Cadmium Thread Series Designator: Unef Shelf Life: N/a Thread Series Designator: Infor Measure:	1	threaded coupling
Thread Size: 0.938 inches Material: Aluminum alloy Auriace Treatment: Cadmium Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demiltarization:	Т	hready Qty Per Inch (tpi):
0.938 inches Material: Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Line Fuite: Cadmium The Cadmium C	2	0 and 20
Material:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:-Denilitarization:	T	hread Size:
Aluminum alloy Surface Treatment: Cadmium Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt of Measure: Denilitarization:	0	.938 inches
Surface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:	N	laterial:
Cadmium Style Designator: Straight type w/strain relief Straight type w/strain relief Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	Α	luminum alloy
Style Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:	S	Surface Treatment:
Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	C	Cadmium
Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: 	S	tyle Designator:
Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	S	traight type w/strain relief
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	S	Surface Treatment:
Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	C	Cadmium
Shelf Life: N/a Unit Of Measure: Demilitarization:	Т	hread Series Designator:
N/a Unit Of Measure: Demilitarization:	ι	Inef
Unit Of Measure: Demilitarization:	S	helf Life:
 Demilitarization:	Ν	l/a
Demilitarization:	ι	Init Of Measure:
No	C	Demilitarization:
	Ν	lo

NSN 5935-01-020-2579

Electrical Connector Backshell - Page 2 of 2

Fiig: A10100

