# NSN 5935-01-020-6465

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-020-6465

## **Body Style:**

Straight shape, internal coupling

## **Overall Length:**

1.026 inches

## **Overall Diameter:**

1.406 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

18-35 single mating end

## Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

100.0 and 128.0 and 228.0 and 265.0 and 330.0

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

# Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### Contact Surface Treatment:

Gold single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium

#### Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

#### **Included Contact Quantity:**

66 single mating end single contact grouping

NSN 5935-01-020-6465 Electrical Plug Connector - Page 2 of 2 AeroBase Group

# Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.066 gold grains, troy

Precious Material:

Gold

# Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27473 government standard

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.