NSN 5935-01-020-6481

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-020-6481	
Thread Class:	
2a and 2b and 2a	
Thread Direction:	
Right-hand and right-hand and right-hand	
Body Style:	
Straight shape	
Overall Length:	
0.870 inches	
Overall Height:	
0.630 inches	
Overall Width:	
0.190 inches	
Environmental Protection:	
Shock proof and vibration resistant	
Distance Between Mounting Facility Centers:	
0.656 inches	
Threaded Device Type:	
Coupling facility and mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
2 rows of contacts non-inserted board single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
3.0 single mating end single contact grouping	
Polarization Method:	
Jackscrew	
Connector Locking Method:	
Jackscrew-socket	
Thread Length:	
0.150 inches	
Thready Qty Per Inch (tpi):	
56 and 56 and 56	
Thread Size:	
0.086 inches and 0.086 inches and 0.086 inches	

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-020-6481

Electrical Receptacle Connector - Page 2 of 2



Insert	1/1040	امان	
mserr	WATE	паі	-

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-p-330 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.