## NSN 5935-01-020-9545

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-020-9545 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape center screwlock **Overall Length:** 2.125 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches **Overall Height:** 1.860 inches **Overall Width:** 0.830 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Screw Thread Length: 0.340 inches **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** 

Contact Curiace Treatment Opecinication.

Mil-g-45204, type 1 military specification single treatment response single mating end single contact grouping

## NSN 5935-01-020-9545

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-28748/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):