

View Online at <https://aerobasegroup.com/nsn/5935-01-020-9563>

Body Style:

Straight shape w/cable clamp

Bushing Diameter:

0.500 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.136 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.531 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.531 inches

Cable Entrance Diameter:

0.067 inches

Distance From Mounting Shoulder To Front Face:

0.594 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0